



AH-0316

Multi-Purpose Combination Heat Detector

Specifications

Model	AH-0316-2	AH-0316-3	AH-0316-4
Voltage Range	12 ~ 30V DC		
Standby Current	45μA		
Alarm Current @24V DC 470Ω	30mA	35mA	40mA
Thermal Setting	58°C		
Response Grade	Comply to EN54, Grade 1		
Ambient Temperature	-10°C ~ +55°C		
Material	Fire-proof plastic		
Dimensions	102mm(Dia.) x 58mm(H)		
Weight	145g	147g	160g
Color	White		

Order information

AH-0316-2	2-wire
AH-0316-3	3-wire with remote indicator output
AH-0316-4	4-wire with relay output

Specifications (Resettable)


Model	AH-0316-S
Alarm Current	35mA
Standby Current	30μA
Voltage Range	12V DC
Weight	157g

Order information (Resettable)

AH-0316-S	+ Relay Output
-----------	----------------

Effective alert area

Construction/Height	Under 4M	4M ~ 8M
Fire-proof Building	90 M ²	45 M ²
Ordinary Building	50 M ²	30 M ²



EN54  
506c/01/02/03

Distributor in Vietnam:

VIET BAO FIREFIGHTING AND PREVENTING EQUIPMENT COMPANY LIMITED.



140 Nguyen Van Thu St (Ground floor), DaKao ward, Dist.1, HCMC.

Tel: 84.28.39101156 – 39101157. Fax: 84.28.39101158

Email: vietbao@vietbaopccc.com.vn Website: <http://vietbaopccc.com.vn>